



SECTOR TRIPLESPEED takes the name from the three distinct rotation speeds. The diffusion of synthetic materials required an intermediate speed to avoid to overheat the resin bonded components, with the high risk to become opaque.

10000 rpm

Stock removal and finishing of natural materials (marble, granite...)

6000 rpm

Stock removal and finishing of synthetic materials

2600 rpm

Polishing of all materials (natural and synthetic) and for angular device



Angular device (optional)

Electronic portable stone router

TECHNICAL FEATURES

- Spindle (stainless steel)
Rotation speeds: 2600, 6000 or 10000 rpm
Rise and fall: 35 mm
- Frame: die-casted aluminium housing
- Power: 2,2 kW
- Supply tensions: 230V/50-60Hz single phase
- Ground fault interrupter
- Machine: 350 x 550 x 350 mm, 33 kg
- Power unit: 370 x 470 x 230 mm, 15 kg

Packing
In carton box



FEATURES

High power, constant torque

SECTOR TRIPLESPEED is equipped with an electronic vectorial inverter to optimize the supplied power, maintaining constant the torque at any rpm.

Universal supply tension

Even if equipped with a three phase motor, SECTOR TRIPLESPEED is run by single phase 230V/50-60Hz tension, therefore it can be plugged into standard single phase outlets.

STANDARD SUPPLY

- use and maintenance manual with warranty certificate
- service wrenches
- set of bolts for shaped wheels
- spare fuses
- waterproof apron



Aquaplaning



Aquawheel

GLIDING SYSTEMS

Two gliding systems

You can choose between one of the two available different gliding systems, easy interchangeable.

...no scratches on the slab anyway!